



VMCE_V9^{Q&As}

VEEAM Certified Engineer (VMCE9)

Pass Veeam VMCE_V9 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/vmce_v9.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Veeam
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which statements regarding Guest OS File Recovery are true? (select two)

- A. For FAT, NTFS and ReFS the built-in file-level restore functionality is used.
- B. MultiOS file-level recovery allows reading data from ReiserFS, JFS, JFFS2 and XFS
- C. MultiOS file-level recovery allows reading data from 18 different file systems.
- D. When performing recovery through the FTP server, you can recover files with correct permissions.
- E. When performing recovery directly to a Linux host, you can recover files with correct permissions.

Correct Answer: AD

QUESTION 2

Which of the following statements are true when utilizing a Microsoft Hyper-V Off-Host Backup Proxy? (Choose two)

- A. Hyper-V Nano Server is supported when utilizing Hardware VSS
- B. The version of the Hyper-V host and the Off-Host Backup Proxy must match
- C. Veeam Backup from Storage Snapshots must be enabled
- D. Hyper-V must be Windows 2012 or newer
- E. The Hardware VSS provider must be configured

Correct Answer: BE

QUESTION 3

Which cryptographic algorithm is used in Veeam Backup and Replication for backup-to-disk backup files?

- A. RSA
- B. AES-256
- C. Blowfish
- D. MD5
- E. DES

Correct Answer: B

QUESTION 4



Using Hyper-V offhost proxy has the following requirements? (Select three)

- A. Shared storage must be HP StoreVirtual, HP StoreVirtual VSA or HP StoreServ (3PAR)
- B. Offhost Proxy must have VSS hardware provider installed. This VSS hardware provider is supplied by storage vendor.
- C. Offhost Proxy must have access to shared storage
- D. Offhost Proxy must have Hyper-V role enabled
- E. Offhost Proxy must have VSS hardware provider installed. This VSS hardware provider is supplied by Veeam limiting it to specific vendors.

Correct Answer: ABC

QUESTION 5

Which component is used by Veeam Backup and Replication to transfer data from the Veeam Backup Proxy to an HPE StoreOnce deduplication appliance?

- A. Proxy appliance
- B. HPE Catalyst
- C. Gateway server
- D. VeeamZIP
- E. Backup repository

Correct Answer: C

Reference

https://helpcenter.veeam.com/docs/backup/vsphere/deduplicating_appliance_storeonce.html?ver=95

[VMCE_V9 PDF Dumps](#)

[VMCE_V9 Study Guide](#)

[VMCE_V9 Braindumps](#)