



# 1Y0-230<sup>Q&As</sup>

Citrix NetScaler 12 Essentials and Unified Gateway

## Pass Citrix 1Y0-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1y0-230.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which Citrix ADC hardware or software platform offers a Multi-Tenant solution?

- A. VPX
- B. CPX
- C. MPX
- D. SDX

Correct Answer: D

Reference: [https://www.citrix.com/content/dam/citrix/en\\_us/documents/products-solutions/maximizingmulti-tenancy-with-citrix-netScaler-en.pdf](https://www.citrix.com/content/dam/citrix/en_us/documents/products-solutions/maximizingmulti-tenancy-with-citrix-netScaler-en.pdf)

---

### QUESTION 2

Which two options should a Citrix Administrator consider when adding a secondary device in a high availability (HA) pair? (Choose two.)

- A. The Independent Network Configuration (INC) mode should be enabled.
- B. Both the devices should have different SNIP addresses.
- C. The nsroot password should be the same on both nodes.
- D. HA Monitoring should be disabled on all the unused interfaces.
- E. Configure the HA status of the Primary Node as STAYPRIMARY.

Correct Answer: CD

---

### QUESTION 3

Scenario: A Citrix ADC Appliance is having intermittent issues. A Citrix Administrator is unable to identify the root cause and fix them. The administrator opened a Support ticket and the engineer assigned to the case requested all the logs and configuration information from the Citrix ADC.

Which technical support tool can the administrator use to gather all the information on the Citrix ADC to send to the Support Engineer?

- A. Generate Support File
- B. Batch Configuration
- C. Start New Trace
- D. Get Back Trace



---

Correct Answer: A

Reference: <https://support.citrix.com/article/CTX127900>

---

#### QUESTION 4

Where should a Citrix Administrator configure SmartControl restrictions?

- A. Citrix Gateway
- B. XenDesktop Delivery Controller
- C. Citrix Gateway, Citrix Delivery Controller and StoreFront
- D. StoreFront and Citrix Delivery Controller

Correct Answer: A

Reference: <https://docs.citrix.com/en-us/netscaler-gateway/12/integrate-web-interface-apps/smartcontrol.html>

---

#### QUESTION 5

Which three NetScaler features can a Citrix Administrator use for default syntax policies? (Choose three.)

- A. SSL
- B. Rewrite
- C. Integrated caching
- D. Protection
- E. Responder

Correct Answer: ABE

Reference <https://docs.citrix.com/zh-cn/netscaler/11/appexpert/policies-and-expressions/ns-pi-intro-polexp-wrapper-con/ns-pi-adv-class-pol-con.html>

---

#### QUESTION 6

A Citrix Administrator needs to configure a policy where users will be downgraded to 'ICA Proxy Only' from 'Full VPN' in the event a user fails to meet Endpoint Analysis requirements.

Which configuration is required to satisfy this requirement?

- A. Quarantine Group with nFactor authentication
- B. Quarantine Group with two-factor authentication, using LDAP as primary authentication



- C. Quarantine Group with no Active Directory membership
- D. Quarantine Group with regular Active Directory membership

Correct Answer: A

---

#### QUESTION 7

Scenario: A Citrix Administrator found that whenever a NetScaler VPX high availability (HA) pair of appliances fails over, the load-balanced websites are NOT accessible. The administrator investigated the issue and found that the router and switches do NOT support gratuitous ARP (GARP). However, the administrator cannot immediately afford to upgrade the network infrastructure.

What can the administrator do immediately to resolve the issue and prevent a future outage?

- A. Migrate the VPX pair to different hypervisor hosts.
- B. Replace the NetScaler VPX appliances with NetScaler MPX appliances
- C. Configure a Virtual MAC (VMAC) on the NetScaler.
- D. Utilize IPv6 instead of IPv4.

Correct Answer: D

---

#### QUESTION 8

Which NetScaler feature can be utilized to reuse existing TCP connections?

- A. Content Switching
- B. TCP Buffering
- C. Keep Alives
- D. Connection Multiplexing

Correct Answer: D

Explanation: TCP multiplexing is a technique that enables the reuse of existing TCP connections Reference: <https://www.citrix.com/blogs/2012/03/08/connection-multiplexing-in-netscaler/>

---

#### QUESTION 9

Scenario: A Citrix Administrator needs to configure a group in which Contractors will have limited access to internal resources over the SSL VPN. The Contractors group should be able to access all internal IP Addresses but should NOT be able to open SSH connections to any internal resource.

Which expression should the administrator use to satisfy this scenario?



- A. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0andand(REQ.TCP.DESTPORT = = 22) Action set to Allow
- B. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0andand(REQ.TCP.DESTPORT = = 22) Action set to Deny
- C. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0andand(REQ.TCP.DESTPORT = = 80 || REQ.TCP.DESTPORT = = 443)
- D. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0 || (REQ.TCP.DESTPORT = = 22)

Correct Answer: D

#### QUESTION 10

Scenario: A Citrix Administrator is performing a disaster recovery test and decided to fail over the Citrix ADC high availability (HA) pair appliances. The administrator noticed that the failover is NOT working as expected in item text, and the Secondary Citrix ADC is NOT taking over as Primary. The administrator suspects that networking issues may be causing the failure. What could be the cause of this issue with the Citrix ADCs?

- A. HA monitoring is enabled on a disabled interface of the Primary Node
- B. HA monitoring is enabled on an interface of the Secondary Node that shows as ENABLED, DOWN
- C. Independent network configuration (INC) mode is enabled
- D. HA heartbeats are only seen on some enabled interfaces of the Secondary Node

Correct Answer: D

#### QUESTION 11

Scenario: A Citrix Administrator needs to integrate LDAP for Citrix ADC system administration using the current Active Directory groups. The administrator created the group on the Citrix ADC, exactly matching the group name in LDAP.

What can the administrator add next to complete the configuration of the LDAP?

- A. Users to the group on the Citrix ADC
- B. An AAA action to the group
- C. A command policy to the group to specify the permission level
- D. A nested group to the new group

Correct Answer: C

Reference: <https://support.citrix.com/article/CTX123782>



---

### QUESTION 12

Scenario: A Citrix Administrator currently manages a NetScaler environment in a retail company that is growing quickly and may soon double its volume of business. Currently, a NetScaler MPX 5550, which handles web and SSL transactions, is in place, but is closed to full capacity. Due to the forecasted growth increase, the administrator needs to find a cost-effective solution. What can the administrator recommend to management in order to cost effectively handle the growth?

- A. Upgrade to NetScaler MPX 5650
- B. Upgrade to NetScaler MPX 8005
- C. Upgrade to NetScaler SDX 14100
- D. Add a second MPX 5550 appliance

Correct Answer: C

---

### QUESTION 13

Which three pieces of information are required for a NetScaler Unified Gateway deployment? (Choose three.)

- A. Valid SSL Certificates
- B. Secondary Authentication for the Unified Gateway
- C. Enterprise license or higher
- D. Content Switching virtual server
- E. Multiple IP addresses for User Access

Correct Answer: ACD

---

### QUESTION 14

Which two deployment methods does remote desktop protocol (RDP) proxy support? (Choose two.)

- A. ICA proxy
- B. Two hops
- C. Optimal Gateway
- D. CVPN

Correct Answer: AD

Reference: <https://docs.citrix.com/en-us/netscaler-gateway/12/rdp-proxy.html>

---

### QUESTION 15

Scenario: User authentication is failing through the NetScaler. A Citrix Administrator checked the Authentication,



Authorization and Auditing (AAA) policy, action and virtual server and verified that the correct configuration was in place. The administrator bypassed the NetScaler and the authentication worked. Which NetScaler utility can the administrator use to troubleshoot the access issue?

- A. nslog file
- B. aaad.debug
- C. nscon message
- D. Dashboard

Correct Answer: B

[Latest 1Y0-230 Dumps](#)

[1Y0-230 PDF Dumps](#)

[1Y0-230 Exam Questions](#)